



UNITED STATES
NUCLEAR REGULATORY COMMISSION

WASHINGTON, D.C. 20555-0001

January 7, 1999

Mr. Charles H. Cruse
Vice President - Nuclear Energy
Baltimore Gas and Electric Company
Calvert Cliffs Nuclear Power Plant
1650 Calvert Cliffs Parkway
Lusby, MD 20657

SUBJECT: CORRECTION OF A TYPOGRAPHICAL ERROR - LICENSE AMENDMENT NOS.
227 (UNIT 1) AND 201 (UNIT 2) (TAC NOS. MA7166 AND MA7167)

Dear Mr. Cruse:

In your letter of November 4, 1999, you requested a correction of a typographical error discovered in License Amendment Nos. 227 (Unit 1) and 201 (Unit 2) for Operating License Nos. DPR-53 and DPR-69. You indicated that the use of a letter for this type of change is allowed by the Nuclear Regulatory Commission's (NRC's) "Proposed Guidance for Correction of Technical Specification Typographical Errors," SECY-96-238, dated November 19, 1996 (The guidance in SECY-96-238 was approved in a Staff Requirements Memorandum dated December 17, 1996).

The correction of the typographical error is related to Technical Specifications (TSs) 3.4.6 and 3.4.7. TSs 3.4.6 and 3.4.7 provide conditions that must be met before a reactor coolant pump can be started in Modes 4 and 5, respectively. Those conditions are provided to ensure that a pressure excursion does not occur in the reactor coolant system (RCS) as a result of starting reactor coolant pumps when either or both steam generators are hotter than the reactor.

When Baltimore Gas and Electric Company (BGE) submitted a license amendment for adopting the Improved Standard Technical Specifications (ISTS), BGE included markups for TSs 3.4.6 and 3.4.7. These markups retained the requirement that the temperature of each steam generator must be less than or equal to 30 °F above the RCS temperature. In the approved pages for the ISTS conversion, the term "RCS temperature" was inadvertently changed to "RCS cold leg temperature." Calvert Cliffs low temperature overpressure protection analysis uses RCS bulk average temperature, not cold leg temperature, as a criterion for this condition.

The guidance in SECY 96-238 allows for use of an administrative letter to correct a typographical error provided that 1) the error was introduced inadvertently in a particular license amendment; and 2) the erroneous change was not addressed in the notice to the public nor reviewed by the NRC staff. BGE has determined that the error occurred in License Amendment Nos. 227 and 201. This satisfied the first requirement. The use of the term "RCS temperature" with regard to starting the reactor cooling pumps was approved by the NRC in low temperature overpressure protection License Amendment Nos. 145 (Unit 1) and 131 (Unit 2). Since the wording in the markups related to TS 3.4.6 and 3.4.7 did not change in License Amendment Nos. 227 and 201, it was not subject to NRC review in those amendments and it was not identified in any notice on the amendment published in the Federal Register (63 FR 27768). This satisfied the second requirement.

PDR A DOCK


DF01

C. Cruse

- 2 -

The staff has reviewed the license request to correct the typographical error in accordance with the guidance in SECY 96-238. Based on our review, as set forth above, we have determined that the use of an administrative letter to correct the typographical error is acceptable. Enclosed are the corrected TS pages.

Sincerely,



Alexander W. Dromerick, Sr. Project Manager, Section 1
Project Directorate I
Division of Licensing Project Management
Office of Nuclear Reactor Regulation

Docket Nos. 50-317 and 50-318

Enclosure: As stated

cc w/encl: See next page

Calvert Cliffs Nuclear Power Plant
Unit Nos. 1 and 2

President
Calvert County Board of
Commissioners
175 Main Street
Prince Frederick, MD 20678

James P. Bennett, Esquire
Counsel
Baltimore Gas and Electric Company
P.O. Box 1475
Baltimore, MD 21203

Jay E. Silberg, Esquire
Shaw, Pittman, Potts, and Trowbridge
2300 N Street, NW
Washington, DC 20037

Mr. Bruce S. Montgomery, Director
NRM
Calvert Cliffs Nuclear Power Plant
1650 Calvert Cliffs Parkway
Lusby, MD 20657-4702

Resident Inspector
U.S. Nuclear Regulatory
Commission
P.O. Box 287
St. Leonard, MD 20685

Mr. Richard I. McLean, Manager
Nuclear Programs
Power Plant Research Program
Maryland Dept. of Natural Resources
Tawes State Office Building, B3
Annapolis, MD 21401

Regional Administrator, Region I
U.S. Nuclear Regulatory Commission
475 Allendale Road
King of Prussia, PA 19406

Mr. Joseph H. Walter, Chief Engineer
Public Service Commission of
Maryland
Engineering Division
6 St. Paul Centre
Baltimore, MD 21202-6806

Kristen A. Burger, Esquire
Maryland People's Counsel
6 St. Paul Centre
Suite 2102
Baltimore, MD 21202-1631

Patricia T. Birnie, Esquire
Co-Director
Maryland Safe Energy Coalition
P.O. Box 33111
Baltimore, MD 21218

Mr. Loren F. Donatell
NRC Technical Training Center
5700 Brainerd Road
Chattanooga, TN 37411-4017

3.4 REACTOR COOLANT SYSTEM (RCS)

3.4.6 RCS Loops - MODE 4

LCO 3.4.6 Two loops consisting of any combination of RCS loops and shutdown cooling (SDC) loops shall be OPERABLE and at least one loop shall be in operation.

----- NOTES-----

1. All reactor coolant pumps and SDC pumps may be not in operation for ≤ 1 hour per 8 hour period, provided:
 - a. No operations are permitted that would cause reduction of the RCS boron concentration; and
 - b. Core outlet temperature is maintained at least 10°F below saturation temperature.
2. No reactor coolant pump shall be started with any RCS cold leg temperature $\leq 365^{\circ}\text{F}$ (Unit 1), $\leq 301^{\circ}\text{F}$ (Unit 2) unless:
 - a. Pressurizer water level is ≤ 170 inches;
 - b. Pressurizer pressure is ≤ 300 psia (Unit 1), ≤ 320 psia (Unit 2); and
 - c. Secondary side water temperature in each steam generator is $\leq 30^{\circ}\text{F}$ above the RCS temperature.

APPLICABILITY: MODE 4.

3.4 REACTOR COOLANT SYSTEM (RCS)

3.4.7 RCS Loops - MODE 5, Loops Filled

LCO 3.4.7 One shutdown cooling (SDC) loop shall be OPERABLE and in operation, and either:

- a. One additional SDC loop shall be OPERABLE; or
- b. The secondary side water level of each steam generator (SG) shall be ≥ -50 inches.

----- NOTES-----

1. The SDC pump of the loop in operation may be not in operation for ≤ 1 hour per 8 hour period provided:
 - a. No operations are permitted that would cause reduction of the RCS boron concentration; and
 - b. Core outlet temperature is maintained at least 10°F below saturation temperature.
2. One required SDC loop may be inoperable for up to 2 hours for surveillance testing provided that the other SDC loop is OPERABLE and in operation.
3. No reactor coolant pump shall be started with any RCS cold leg temperature $\leq 365^{\circ}\text{F}$ (Unit 1), $\leq 301^{\circ}\text{F}$ (Unit 2) unless:
 - a. The pressurizer water level is ≤ 170 inches;
 - b. Pressurizer pressure is ≤ 300 psia (Unit 1), ≤ 320 psia (Unit 2); and
 - c. The secondary side water temperature in each SG is $\leq 30^{\circ}\text{F}$ above the RCS temperature.
4. All SDC loops may be not in operation during planned heatup to MODE 4 when at least one RCS loop is in operation.

C. Cruse

- 2 -

January 7, 1999

The staff has reviewed the license request to correct the typographical error in accordance with the guidance in SECY 96-238. Based on our review, as set forth above, we have determined that the use of an administrative letter to correct the typographical error is acceptable. Enclosed are the corrected TS pages.

Sincerely,

Original signed by:

Alexander W. Dromerick, Sr. Project Manager, Section 1
Project Directorate I
Division of Licensing Project Management
Office of Nuclear Reactor Regulation

Docket Nos. 50-317 and 50-318

Enclosure: As stated

cc w/encl: See next page

DISTRIBUTION:

File Center

PUBLIC

PDI-1 R/F

E. Adensam (EGA1)

S. Peterson

S. Little

A. Dromerick

OGC

G. Hill (4)

W. Beckner

M. Oprendek, RI

DOCUMENT NAME: G:\PDI-1\CC1-2\CORLTRMA7166.WPD

*See previous concurrence

To receive a copy of this document, indicate in the box: "C" = Copy without attachment/enclosure "E" = Copy with attachment/enclosure "N" = No copy

OFFICE	PM:PDI-1	E	LA:PDI-1	SE:PDI-1	OGC*
NAME	ADromerick/rs1		SLittle	SPeterson	RWeisman
DATE	12/17/99		12/15/99	12/14/99	12/10/99

Official Record Copy