
TABLE OF CONTENTS

| <u>Section</u> | <u>Title</u> | <u>Page</u> |
|----------------|---|-------------|
| CHAPTER 4 | REACTOR | 4.1-1 |
| 4.1 | Summary Description | 4.1-1 |
| 4.1.1 | Principal Design Requirements | 4.1-4 |
| 4.1.2 | Combined License Information | 4.1-5 |
| 4.1.3 | References | 4.1-5 |
| 4.2 | Fuel System Design | 4.2-1 |
| 4.2.1 | Design Basis | 4.2-2 |
| 4.2.1.1 | Cladding | 4.2-3 |
| 4.2.1.2 | Fuel Material | 4.2-4 |
| 4.2.1.3 | Fuel Rod Performance | 4.2-4 |
| 4.2.1.4 | Spacer Grids | 4.2-5 |
| 4.2.1.5 | Fuel Assembly Structural Design | 4.2-5 |
| 4.2.1.6 | In-core Control Components | 4.2-7 |
| 4.2.1.7 | Surveillance Program | 4.2-9 |
| 4.2.2 | Description and Design Drawings | 4.2-9 |
| 4.2.2.1 | Fuel Rods | 4.2-10 |
| 4.2.2.2 | Fuel Assembly Structure | 4.2-11 |
| 4.2.2.3 | In-core Control Components | 4.2-16 |
| 4.2.3 | Design Evaluation | 4.2-20 |
| 4.2.3.1 | Cladding | 4.2-21 |
| 4.2.3.2 | Fuel Materials Considerations | 4.2-23 |
| 4.2.3.3 | Fuel Rod Performance | 4.2-24 |
| 4.2.3.4 | Spacer Grids | 4.2-28 |
| 4.2.3.5 | Fuel Assembly | 4.2-28 |
| 4.2.3.6 | Reactivity Control Assemblies and Burnable Absorber Rods | 4.2-30 |
| 4.2.4 | Testing and Inspection Plan | 4.2-32 |
| 4.2.4.1 | Quality Assurance Program | 4.2-32 |
| 4.2.4.2 | Quality Control | 4.2-33 |
| 4.2.4.3 | Letdown Radiation Monitoring | 4.2-35 |
| 4.2.4.4 | In-core Control Component Testing and Inspection | 4.2-35 |
| 4.2.4.5 | Tests and Inspections by Others | 4.2-36 |
| 4.2.4.6 | Inservice Surveillance | 4.2-36 |
| 4.2.4.7 | Onsite Inspection | 4.2-37 |
| 4.2.5 | Combined License Information | 4.2-37 |
| 4.2.6 | References | 4.2-37 |
| 4.3 | Nuclear Design | 4.3-1 |
| 4.3.1 | Design Basis | 4.3-1 |

TABLE OF CONTENTS (Cont.)

| <u>Section</u> | <u>Title</u> | <u>Page</u> |
|----------------|---|-------------|
| | 4.3.1.1 Fuel Burnup | 4.3-2 |
| | 4.3.1.2 Negative Reactivity Feedbacks (Reactivity Coefficients) . . . | 4.3-3 |
| | 4.3.1.3 Control of Power Distribution | 4.3-3 |
| | 4.3.1.4 Maximum Controlled Reactivity Insertion Rate | 4.3-4 |
| | 4.3.1.5 Shutdown Margins | 4.3-5 |
| | 4.3.1.6 Stability | 4.3-6 |
| | 4.3.1.7 Anticipated Transients without SCRAM (ATWS) | 4.3-7 |
| 4.3.2 | Description | 4.3-7 |
| | 4.3.2.1 Nuclear Design Description | 4.3-7 |
| | 4.3.2.2 Power Distribution | 4.3-9 |
| | 4.3.2.3 Reactivity Coefficients | 4.3-20 |
| | 4.3.2.4 Control Requirements | 4.3-24 |
| | 4.3.2.5 Control Rod Patterns and Reactivity Worth | 4.3-30 |
| | 4.3.2.6 Criticality of the Reactor During Refueling | 4.3-31 |
| | 4.3.2.7 Stability | 4.3-33 |
| | 4.3.2.8 Vessel Irradiation | 4.3-38 |
| 4.3.3 | Analytical Methods | 4.3-38 |
| | 4.3.3.1 Fuel Temperature (Doppler) Calculations | 4.3-39 |
| | 4.3.3.2 Macroscopic Group Constants | 4.3-40 |
| | 4.3.3.3 Spatial Few-Group Diffusion Calculations | 4.3-41 |
| 4.3.4 | Combined License Information | 4.3-42 |
| 4.3.5 | References | 4.3-43 |
| 4.4 | Thermal and Hydraulic Design | 4.4-1 |
| | 4.4.1 Design Basis | 4.4-1 |
| | 4.4.1.1 Departure from Nucleate Boiling Design Basis | 4.4-1 |
| | 4.4.1.2 Fuel Temperature Design Basis | 4.4-3 |
| | 4.4.1.3 Core Flow Design Basis | 4.4-3 |
| | 4.4.1.4 Hydrodynamic Stability Design Basis | 4.4-4 |
| | 4.4.1.5 Other Considerations | 4.4-4 |
| 4.4.2 | Description of Thermal and Hydraulic Design of the Reactor Core | 4.4-4 |
| | 4.4.2.1 Summary Comparison | 4.4-4 |
| | 4.4.2.2 Critical Heat Flux Ratio or DNBR and Mixing Technology | 4.4-4 |
| | 4.4.2.3 Linear Heat Generation Rate | 4.4-10 |
| | 4.4.2.4 Void Fraction Distribution | 4.4-10 |
| | 4.4.2.5 Core Coolant Flow Distribution | 4.4-10 |
| | 4.4.2.6 Core Pressure Drops and Hydraulic Loads | 4.4-11 |
| | 4.4.2.7 Correlation and Physical Data | 4.4-12 |
| | 4.4.2.8 Thermal Effects of Operational Transients | 4.4-14 |
| | 4.4.2.9 Uncertainties in Estimates | 4.4-14 |
| | 4.4.2.10 Flux Tilt Considerations | 4.4-16 |

TABLE OF CONTENTS (Cont.)

| <u>Section</u> | <u>Title</u> | <u>Page</u> |
|----------------|--|-------------|
| | 4.4.2.11 Fuel and Cladding Temperatures | 4.4-17 |
| 4.4.3 | Description of the Thermal and Hydraulic Design of the Reactor Coolant System | 4.4-20 |
| | 4.4.3.1 Plant Configuration Data | 4.4-20 |
| | 4.4.3.2 Operating Restrictions on Pumps | 4.4-20 |
| | 4.4.3.3 Power-Flow Operating Map (Boiling Water Reactor [BWR]) | 4.4-20 |
| | 4.4.3.4 Temperature-Power Operating Map (PWR) | 4.4-21 |
| | 4.4.3.5 Load Following Characteristics | 4.4-21 |
| | 4.4.3.6 Thermal and Hydraulic Characteristics Summary Table | 4.4-21 |
| 4.4.4 | Evaluation | 4.4-21 |
| | 4.4.4.1 Critical Heat Flux | 4.4-21 |
| | 4.4.4.2 Core Hydraulics | 4.4-21 |
| | 4.4.4.3 Influence of Power Distribution | 4.4-23 |
| | 4.4.4.4 Core Thermal Response | 4.4-25 |
| | 4.4.4.5 Analytical Methods | 4.4-25 |
| | 4.4.4.6 Hydrodynamic and Flow Power Coupled Instability | 4.4-27 |
| | 4.4.4.7 Fuel Rod Behavior Effects from Coolant Flow Blockage | 4.4-29 |
| 4.4.5 | Testing and Verification | 4.4-30 |
| | 4.4.5.1 Tests Prior to Initial Criticality | 4.4-30 |
| | 4.4.5.2 Initial Power and Plant Operation | 4.4-31 |
| | 4.4.5.3 Component and Fuel Inspections | 4.4-31 |
| 4.4.6 | Instrumentation Requirements | 4.4-31 |
| | 4.4.6.1 Incore Instrumentation | 4.4-31 |
| | 4.4.6.2 Overtemperature and Overpower ΔT Instrumentation | 4.4-32 |
| | 4.4.6.3 Instrumentation to Limit Maximum Power Output | 4.4-32 |
| | 4.4.6.4 Digital Metal Impact Monitoring System | 4.4-33 |
| 4.4.7 | Combined License Information | 4.4-35 |
| 4.4.8 | References | 4.4-35 |
| 4.5 | Reactor Materials | 4.5-1 |
| | 4.5.1 Control Rod and Drive System Structural Materials | 4.5-1 |
| | 4.5.1.1 Materials Specifications | 4.5-1 |
| | 4.5.1.2 Fabrication and Processing of Austenitic Stainless Steel Components | 4.5-2 |
| | 4.5.1.3 Other Materials | 4.5-2 |
| | 4.5.1.4 Contamination Protection and Cleaning of Austenitic Stainless Steel | 4.5-3 |

TABLE OF CONTENTS (Cont.)

| <u>Section</u> | <u>Title</u> | <u>Page</u> |
|----------------|--|-------------|
| 4.5.2 | Reactor Internal and Core Support Materials | 4.5-3 |
| 4.5.2.1 | Materials Specifications | 4.5-3 |
| 4.5.2.2 | Controls on Welding | 4.5-3 |
| 4.5.2.3 | Nondestructive Examination of Tubular Products and Fittings | 4.5-4 |
| 4.5.2.4 | Fabrication and Processing of Austenitic Stainless Steel Components | 4.5-4 |
| 4.5.2.5 | Contamination Protection and Cleaning of Austenitic Stainless Steel | 4.5-4 |
| 4.5.3 | Combined License Information | 4.5-4 |
| 4.5.4 | References | 4.5-4 |
| 4.6 | Functional Design of Reactivity Control Systems | 4.6-1 |
| 4.6.1 | Information for Control Rod Drive System | 4.6-1 |
| 4.6.2 | Evaluations of the Control Rod Drive System | 4.6-1 |
| 4.6.3 | Testing and Verification of the Control Rod Drive System | 4.6-2 |
| 4.6.4 | Information for Combined Performance of Reactivity Systems | 4.6-2 |
| 4.6.5 | Evaluation of Combined Performance | 4.6-3 |
| 4.6.6 | Combined License Information | 4.6-4 |

LIST OF TABLES

| <u>Table No.</u> | <u>Title</u> | <u>Page</u> |
|------------------|---|-------------|
| 4.1-1 | Reactor Design Comparison Table (Sheets 1 - 3) | 4.1-6 |
| 4.1-2 | Analytical Techniques in Core Design (Sheets 1 - 2) | 4.1-9 |
| 4.1-3 | Design Loading Conditions for Reactor Core Components | 4.1-11 |
| 4.3-1 | Reactor Core Description (First Cycle) (Sheets 1 - 3) | 4.3-48 |
| 4.3-2 | Nuclear Design Parameters (First Cycle) (Sheets 1 - 2) | 4.3-51 |
| 4.3-3 | Reactivity Requirements for Rod Cluster Control Assemblies | 4.3-53 |
| 4.3-4 | Benchmark Critical Experiments | 4.3-54 |
| 4.3-5 | Stability Index for Pressurized Water Reactor Cores with a 12-Foot Height | 4.3-55 |
| 4.3-6 | Typical Neutron Flux Levels (n/cm ² /s) at Full Power | 4.3-56 |
| 4.3-7 | Comparison of Measured and Calculated Doppler Defects | 4.3-57 |
| 4.3-8 | Comparison of Measured and Calculated Ag-In-Cd Rod Worth | 4.3-58 |
| 4.3-9 | Comparison of Measured and Calculated Moderator Coefficients at HZP, BOL | 4.3-59 |
| 4.4-1 | Thermal and Hydraulic Comparison Table (AP600 and a Typical Westinghouse Four-Loop Plant) (Sheets 1 - 2) | 4.4-42 |

LIST OF FIGURES

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|---|-------------|
| 4.2-1 | Fuel Assembly Cross-Section | 4.2-40 |
| 4.2-2 | Fuel Assembly Outline | 4.2-41 |
| 4.2-3 | Fuel Rod Schematic | 4.2-43 |
| 4.2-4 | Top Grid Sleeve Detail | 4.2-44 |
| 4.2-5 | Intermediate Grid to Thimble Attachment Joint | 4.2-45 |
| 4.2-6 | Intermediate Flow Mixer Grid to Thimble Attachment | 4.2-46 |
| 4.2-7 | Grid Thimble to Bottom Nozzle Joint | 4.2-47 |
| 4.2-8 | Rod Cluster Control and Drive Rod Assembly with Interfacing Components | 4.2-48 |
| 4.2-9 | Rod Cluster Control Assembly | 4.2-49 |
| 4.2-10 | Absorber Rod Detail | 4.2-50 |
| 4.2-11 | Gray Rod Cluster Assembly | 4.2-51 |
| 4.2-12 | Wet Annular Burnable Absorber Assembly | 4.2-52 |
| 4.2-13 | Wet Annular Burnable Absorber Rod Detail | 4.2-53 |
| 4.2-14 | Primary Source Assembly | 4.2-54 |
| 4.2-15 | Secondary Source Assembly | 4.2-55 |
| 4.3-1 | Fuel Loading Arrangement | 4.3-60 |
| 4.3-2 | Typical Production and Consumption of Higher Isotopes | 4.3-61 |
| 4.3-3 | Cycle 1 Soluble Boron Concentration Versus Burnup | 4.3-62 |
| 4.3-4a | Cycle 1 Assembly Burnable Absorber Patterns | 4.3-63 |
| 4.3-4b | Cycle 1 Assembly Burnable Absorber Patterns | 4.3-64 |
| 4.3-5 | Burnable Absorber, Primary, and Secondary Source Assembly Locations | 4.3-65 |
| 4.3-6 | Normalized Power Density Distribution Near Beginning of Life, Unrodded Core, Hot Full Power, No Xenon | 4.3-66 |
| 4.3-7 | Normalized Power Density Distribution Near Beginning of Life, Unrodded Core, Hot Full Power, Equilibrium Xenon | 4.3-67 |
| 4.3-8 | Normalized Power Density Distribution Near Beginning of Life, Gray Bank M0 Inserted, Hot Full Power, Equilibrium Xenon | 4.3-68 |
| 4.3-9 | Normalized Power Density Distribution Near Middle of Life, Unrodded Core, Hot Full Power, Equilibrium Xenon | 4.3-69 |
| 4.3-10 | Normalized Power Density Distribution Near End of Life, Unrodded Core, Hot Full Power, Equilibrium Xenon | 4.3-70 |
| 4.3-11 | Normalized Power Density Distribution Near End of Life, Gray Bank M0 Inserted, Hot Full Power, Equilibrium Xenon | 4.3-71 |
| 4.3-12 | Rodwise Power Distribution in a Typical Assembly (F-8) Near Beginning of Life, Hot Full Power, Equilibrium Xenon, Unrodded Core | 4.3-72 |

LIST OF FIGURES (Cont.)

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|---|-------------|
| 4.3-13 | Rodwise Power Distribution in a Typical Assembly (F-8) Near End of Life, Hot Full Power, Equilibrium Xenon, Unrodded Core | 4.3-73 |
| 4.3-14 | Maximum F_Q x Power Versus Axial Height During Normal Operation | 4.3-74 |
| 4.3-15 | Comparison Between Calculated and Measured Relative Fuel Assembly Power Distribution | 4.3-75 |
| 4.3-16 | Typical Calculated Versus Measured Axial Power Distribution | 4.3-76 |
| 4.3-17 | Measured F_Q Values Versus Axial Offset for Full Power Rod Configurations | 4.3-77 |
| 4.3-18 | Typical Doppler Temperature Coefficient at BOL and EOL | 4.3-78 |
| 4.3-19 | Typical Doppler-Only Power Coefficient at BOL and EOL | 4.3-79 |
| 4.3-20 | Typical Doppler-Only Power Defect at BOL and EOL | 4.3-80 |
| 4.3-21 | Typical Moderator Temperature Coefficient at BOL, Unrodded | 4.3-81 |
| 4.3-22 | Typical Moderator Temperature Coefficient at EOL | 4.3-82 |
| 4.3-23 | Typical Moderator Temperature Coefficient as a Function of Boron Concentration at BOL, Unrodded | 4.3-83 |
| 4.3-24 | Typical Hot Full Power Temperature Coefficient Versus Cycle Burnup | 4.3-84 |
| 4.3-25 | Typical Total Power Coefficient at BOL and EOL | 4.3-85 |
| 4.3-26 | Typical Total Power Defect at BOL and EOL | 4.3-86 |
| 4.3-27 | Rod Cluster Control Assembly Pattern | 4.3-87 |
| 4.3-28 | Typical Accidental Simultaneous Withdrawal of Two Control Banks at EOL, HZP, Moving in the Same Plane | 4.3-88 |
| 4.3-29 | Typical Design Trip Curve | 4.3-89 |
| 4.3-30 | Typical Normalized Rod Worth Versus Percent Insertion All Rods Inserting Less Most Reactive Stuck Rod | 4.3-90 |
| 4.3-31 | X-Y Xenon Test Thermocouple Response Quadrant Tilt Difference Versus Time | 4.3-91 |
| 4.3-32 | Calculated and Measured Doppler Defect and Coefficients at BOL, Two-Loop Plant, 121 Assemblies, 12-Foot Core | 4.3-92 |
| 4.4-1 | Thermal Diffusion Coefficient (TDC) versus Reynolds Number for 26-Inch Grid Spacing | 4.4-44 |
| 4.4-2 | Void Fraction versus Thermodynamic Quality | 4.4-45 |
| 4.4-3 | Thermal Conductivity of Uranium Dioxide | 4.4-46 |