

Telephone (856) 797-0900 Fax (856) 797-0909

Amssor Public

BY OVERNIGHT MAIL

March 16, 2000

U.S. Nuclear Regulatory Commission ATTN: Document Control Desk Washington, DC 20555-0001

Subject:USNRC Docket No. 71-9261; TAC No. L22085HI-STAR 100 Transportation CoC 9261License Amendment Request 9261-1, Supplement 5

References:

Holtec Project 5014
Holtec Letter to NRC dated November 24,1999, LAR 9261-1

Dear Sir:

As discussed during our conversation with the NRC project manager yesterday, enclosed please find two sketches of the TN-designed damaged fuel and thoria rod canisters for Dresden Unit 1. These sketches are proposed to be included in Chapter 1 of the HI-STAR 100 transportation Safety Analysis Report (SAR) in lieu of including all of the detailed fabrication drawings submitted for review last November in the SAR and the Certificate of Compliance (CoC). Also included are revised pages from the CoC that delete reference to these drawings as an integral part of the CoC.

If you have any questions or require additional information, please contact us.

Sincerely,

Brian Gutherman, P.E. Licensing Manager

cc: Mr. Mark Delligatti, USNRC (w/attach.) Ms. Marissa Bailey, USNRC (w/attach.)

Document ID: 5014382

Approval:

10 P 1 mg4

K.P. Singh, Ph.D, P.E. President and CEO



Holtec Center, 555 Lincoln Drive West, Marlton, NJ 08053

Telephone (856) 797-0900 Fax (856) 797-0909

U. S. Nuclear Regulatory Commission ATTN: Document Control Desk Document ID 5014382 Page 2 of 2

Distribution (w/o attach.):

Recipient

Affiliation

Mr. David Bland	Southern Nuclear Operating Company	
Mr. Ken Phy	New York Power Authority	
Mr. J. Nathan Leech	Commonwealth Edison	
Dr. Max DeLong	Private Fuel Storage	
Mr. Stan Miller	Vermont Yankee Nuclear Power Corporation	
Mr. David Larkin	Energy Northwest	
Mr. Bruce Patton	Pacific Gas & Electric – Diablo Canyon	
Mr. Mark Smith	Pacific Gas & Electric – Humboldt Bay	
Mr. Rodney Pickard	Rodney Pickard American Electric Power	
Mr. Eric Meils	Wisconsin Electric Power Company	
Mr. Paul Plante	Maine Yankee Atomic Power Company	
Mr. Jeff Ellis	Southern California Edison	
Mr. Darrell Williams	Entergy Operations – Arkansas Nuclear One	
Mr. Joe Andrescavage	be Andrescavage GPUN – Oyster Creek Nuclear Power Station	
Mr. Ron Bowker	IES Utilities	
Mr. William Swantz	Nebraska Public Power District	
Mr. Chris Kudla	Entergy Operations – Millstone Unit 1 Decommissioning	
Mr. Keith Waldrop	Duke Power Company	
Mr. Matt Eyre	PECO Energy	
Mr. Al Gould	Florida Power & Light	
Dr. Seymour Raffety	Dairyland Power	
Mr. John Sanchez	Consolidated Edison Company	
Ms. Kathy Picciott	Niagara Mohawk Power Corporation	
Mr. John Donnell	Private Fuel Storage, LLC (SWEC)	
Dr. Stanley Turner	Holtec International, Florida Operations Center	

FIGURE WITHHELD AS SENSITIVE UNCLASSIFIED INFORMATION

FIGURE 1.2.11; TN DAMAGED FUEL CANISTER FOR DRESDEN UNIT-1

REPORT HI-951251

REVISION 9

FIGURE WITHHELD AS SENSITIVE UNCLASSIFIED INFORMATION

FIGURE 1.2.11A; TN THORIA ROD CANISTER FOR DRESDEN UNIT-1

REPORT HI-951251

REVISION 9

Certificate of Compliance No. 9261

Page 2 of 7

Revision 10

Overpack

The HI-STAR 100 overpack is a multi-layer steel cylinder with a welded baseplate and bolted lid (closure plate). The inner shell of the overpack forms an internal cylindrical cavity for housing the MPC. The outer surface of the overpack inner shell is buttressed with intermediate steel shells for radiation shielding. The overpack closure plate incorporates a dual O-ring design to ensure its containment function. The containment system consists of the overpack inner shell, bottom plate, top flange, top closure plate, top closure plate, top closure plate, and drain port plug and seal.

Impact Limiters

The HI-STAR 100 overpack is fitted with two impact limiters fabricated of aluminum honeycomb completely enclosed by an all-welded austenitic stainless steel skin. The two impact limiters are attached to the overpack with 20 and 16 bolts at the top and bottom, respectively.

(3) Drawings

The package shall be constructed and assembled in accordance with drawings listed below which are found in Section 1.4 of Revision 8 of the Holtec HI-STAR Safety Analysis Report (SAR), Rev. 8) Appendix B to this Certificate of Compliance.

(a)	Drawing C1395, Sheets 1- 4, Revision 1 10 Sheet 2-3, Revision 9 Sheet 4, Revision 8	(h) Drawing C1765, Sheets 1-6, Revision 1 12 Sheet 7 s 2-3, Revision 9 0 Sheet 3, Revision 5
(b)	Drawing C1396, Sheets 1-4, 6, Revision 1 12 Sheet 5 s 2-3, Revision 9 0 Sheets 4-5, Revision 8 Sheet 6, Revision 7	Sheet 4, Revision 10 Sheets 5 and 7, Revision 4 Sheet 6, Revision 1
		(i) Drawing C1782, Revision 1
(c)	Drawing C1397, Sheets 1-4, 6, 7, Revision 1 1 Sheet 5 s 2-3, Revision 9 0 Sheets 4, Revision 11	(j) Drawing <i>C</i> 1783, Revision 1
	Sheets 5-7, Revision 8	(k) Drawing C1784, Revision θ 1
(d)	Drawing <i>C</i> 1398, Sheet <i>s</i> 1 <i>-3</i> , Revision <i>1</i> 12 Sheet 2, Revision 9 Sheet 3, Revision 8	(I) Drawing BM- <i>C</i> 1476, Sheet <i>s</i> 1 & 2, Revision 1 12 Sheet 2, Revision 13
		(m) Drawing BM- <i>C</i> 1478, Sheets 1 <i>& 2</i> , Revision 19
(e)	Drawing C1399, Sheets 1-3, Revision 1 10 Sheet 2, Revision 8	Sheet 2, Revision 13
	Sheet 3, Revision 9	(n) Drawing BM- <i>C</i> 1479, Sheets 1 <i>& 2</i> , Revision <i>1</i> 10 Sheet 2, Revision 13
(f)	Drawing C1401, Sheets 1-4, Revision 1 11 Sheets 2 and 4, Revision 8 Sheet 3, Revision 9	(o) Drawing BM- <i>C</i> 1819, Revision 1
(g)	Drawing <i>C</i> 1402, Sheets 1-4, 6, Revision 1 13 Sheet 5 s 2-3, Revision 9 0 Sheets 4-5, Revision 9 Sheet 6, Revision 7	,

Certificate of Compliance No. 9261

Page 3 of 7

Revision 10

5.b. Contents of Packaging

(1) Type and Form, and Quantity of Material

- (a) Fuel assemblies meeting the specifications and quantities provided in Appendix A to this Certificate of Compliance and meeting the requirements provided in items 5.b(1)(b) through 5.b(1)(g) below are authorized for transportation.
- (b) The following definitions apply:

Damaged Fuel Assemblies are fuel assemblies with known or suspected cladding defects, as determined by review of records, greater than pinhole leaks or hairline cracks, missing fuel rods that are not replaced with dummy fuel rods, or those that cannot be handled by normal means. A damaged fuel assembly's inability to *Fuel assemblies which cannot* be handled by normal means must be due to mechanical damage and must not be due to fuel rod cladding damage *are considered fuel debris*.

Damaged Fuel Containers are specially designed fuel containers for damaged fuel assemblies or fuel debris which permit gaseous and liquid media to escape while minimizing dispersal of gross particulates. *DFCs authorized for use in the HI-STAR 100 System are the Holtec design or the Transnuclear Dresden Unit 1 design as shown on the applicable design drawings in the HI-STAR 100 Safety Analysis Report.*

Fuel Debris refers to *is* ruptured fuel rods, severed rods, and loose fuel pellets *or fuel assemblies* with known or suspected defects which cannot be handled by normal means due to fuel cladding damage.

Incore Grid Spacers are fuel assembly grid spacers located within the active fuel region (i.e., not including top and bottom spacers).

Intact Fuel Assemblies are fuel assemblies without known or suspected cladding defects greater than pinhole leaks or hairline cracks and which can be handled by normal means. Partial fuel assemblies, that is fuel assemblies from which fuel rods are missing, shall not be classified as intact fuel assemblies unless dummy fuel rods are used to displace an amount of water greater than or equal to that displaced by the original fuel rod(s).

Minimum Enrichment is the minimum assembly average enrichment. Natural uranium blankets are not considered in determining minimum enrichment.

Planar-Average Initial Enrichment is the simple average of the distributed fuel rod *initial* enrichments within a given axial plane of the assembly lattice.

(c) For MPCs partially loaded with stainless steel clad fuel assemblies, all remaining fuel assemblies in the MPC shall meet the more restrictive of the two limits for the stainless steel clad fuel assemblies

Certificate of Compliance No. 9261

Page 2 of 7

Revision 1

The HI-STAR 100 overpack is a multi-layer steel cylinder with a welded baseplate and bolted lid (closure plate). The inner shell of the overpack forms an internal cylindrical cavity for housing the MPC. The outer surface of the overpack inner shell is buttressed with intermediate steel shells for radiation shielding. The overpack closure plate incorporates a dual O-ring design to ensure its containment function. The containment system consists of the overpack inner shell, bottom plate, top flange, top closure plate, top closure plate, top closure plate, and drain port plug and seal.

Impact Limiters

The HI-STAR 100 overpack is fitted with two impact limiters fabricated of aluminum honeycomb completely enclosed by an all-welded austenitic stainless steel skin. The two impact limiters are attached to the overpack with 20 and 16 bolts at the top and bottom, respectively.

(3) Drawings

The package shall be constructed and assembled in accordance with drawings listed below which are found in Appendix B to this Certificate of Compliance.

- (a) Drawing C1395, Sheets 1-4, Revision 1 (k) Drawing C1784, Revision 1 (b) Drawing C1396, Sheets 1-4, 6, Revision 1 (I) Drawing BM-C1476, Sheets 1 & 2, Revision 1 Sheet 5, Revision 0 (c) Drawing C1397, Sheets 1-4, 6, 7, Revision 1 (m) Drawing BM-C1478, Sheets 1& 2, Revision 1 Sheet 5, Revision 0 (d) Drawing C1398, Sheets 1-3, Revision 1 (n) Drawing BM-C1479, Sheets 1& 2, Revision 1 (e) Drawing C1399, Sheets 1-3, Revision 1 (o) Drawing BM-C1819, Revision 1 (f) Drawing C1401, Sheets 1-4, Revision 1 (g) Drawing C1402, Sheets 1-4, 6, Revision 1 Sheet 5, Revision 0 (h) Drawing C1765, Sheets 1-6, Revision 1 Sheet 7, Revision 0 (i) Drawing C1782, Revision 1
- (j) Drawing C1783, Revision 1