

STPEGS UFSAR

TABLE OF CONTENTS

CHAPTER 6

ENGINEERED SAFETY FEATURES

<u>Section</u>	<u>Title</u>	<u>Page</u>
6.1	ENGINEERED SAFETY FEATURES MATERIALS	6.1-1
6.1.1	Metallic Materials	6.1-1
6.1.2	Organic Materials	6.1-3
6.1.3	Post Accident Chemistry	6.1-5
6.1.4	Post Accident Sump Solution Chemistry Adjustment	6.1-5
6.2	CONTAINMENT SYSTEMS	6.2-1
6.2.1	Containment Functional Design	6.2-1
6.2.2	Containment Heat Removal Systems	6.2-30
6.2.3	Secondary Containment Functional Design (Does not apply to STPEGS)	6.2-42
6.2.4	Containment Isolation System	6.2-42
6.2.5	Combustible Gas Control in Containment	6.2-48
6.2.6	Containment Leakage Testing	6.2-57
6.3	EMERGENCY CORE COOLING SYSTEM	6.3-1
6.3.1	Design Bases	6.3-1
6.3.2	System Design	6.3-2
6.3.3	Performance Evaluation	6.3-17
6.3.4	Tests and Inspections	6.3-25
6.3.5	Instrumentation Requirements	6.3-27
6.4	HABITABILITY SYSTEMS	6.4-1
6.4.1	Design Bases	6.4-1
6.4.2	System Design	6.4-2
6.4.3	System Operational Procedures	6.4-5
6.4.4	Design Evaluation	6.4-5
6.4.5	Testing and Inspection	6.4-7
6.4.6	Instrumentation Requirement	6.4-9
6.5	FISSION PRODUCT REMOVAL AND CONTROL SYSTEMS	6.5-1
6.5.1	Engineered Safety Feature Filter Systems	6.5-1
6.5.2	Containment Spray System - Iodine Removal	6.5-4
6.5.3	Fission Product Control Systems	6.5-8

STPEGS UFSAR

TABLE OF CONTENTS (Continued)

CHAPTER 6

<u>Section</u>	<u>Title</u>	<u>Page</u>
6.6	INSERVICE INSPECTION OF ASME CODE CLASS 2 AND CLASS 3 COMPONENTS	6.6-1
6.6.1	Components Subject to Inspection	6.6-1
6.6.2	Accessibility	6.6-1
6.6.3	Examination Techniques and Procedures	6.6-2
6.6.4	Inspection Intervals	6.6-2
6.6.5	Examination Categories and Requirements	6.6-2
6.6.6	Evaluation of Examination Results	6.6-2
6.6.7	System Pressure Tests	6.6-3
6.6.8	Augmented Inservice Inspection	6.6-3
6.7	MAIN STEAM ISOLATION VALVE LEAKAGE CONTROL SYSTEM	6.7-1

STPEGS UFSAR

LIST OF TABLES

CHAPTER 6

<u>Table</u>	<u>Title</u>	<u>Page</u>
6.1-1	Engineered Safety Features Materials	6.1-7
6.1-3	Protective Coatings on Westinghouse-Supplied Equipment Inside Containment	6.1-11
6.1-4	Coating Schedule for Surfaces Inside Containment (Excluding NSSS Scope of Supply)	6.1-12
6.2.1.1-1	Containment Design Accidents	6.2-63
6.2.1.1-2	DBA Calculated Pressures for Containment	6.2-65
6.2.1.1-3	Containment Data Used in P/T Analysis	6.2-66
6.2.1.1-4	Summary of DBA LOCA Containment Pressure and Temperatures	6.2-67
6.2.1.1-5	Engineered Safety Features System Information	6.2-68
6.2.1.1-7	Modeling of Structural Heat Sinks for MSLB and LOCA P/T Analyses	6.2-70
6.2.1.1-8	Thermophysical Properties of Structural Heat Sinks for LOCA and MSLB Analysis	6.2-73
6.2.1.1-9	Surface Heat Transfer Coefficients	6.2-74
6.2.1.1-10	Accident Chronology for DBA LOCA	6.2-75
6.2.1.1-14	Summary of Containment MSLB Results	6.2-76
6.2.1.1-15	Accident Chronology for DBA MSLB	6.2-77
6.2.1.2-1 (Item G)	Short-Term Mass and Energy Release Rates for Subcompartment Analyses for Pressurizer Spray Line DEG Break	6.2-78
6.2.1.2-1 (Item J)	Short-Term Mass and Energy Release Rates for Subcompartment Analyses for MSLB	6.2-88
6.2.1.2-1 (Item K)	Short-Term Mass and Energy Release Rates for Subcompartment Analyses for Main Feedwater Line Break	6.2-89
6.2.1.2-1 (Item L)	Short-Term Mass and Energy Release Rates for Subcompartment Analyses for CVCS Letdown Line Break - Radioactive Pipe Chase Subcompartment Blowdown	6.2-91
6.2.1.2-1 (Item M)	Short-Term Mass and Energy Release Rates for Subcompartment Analyses for CVCS Letdown Line Break - RHR 1A Valve Room Subcompartment Analyses	6.2-92
6.2.1.2-1 (Item N)	Short-Term Mass and Energy Release Rates for Subcompartment Analyses for CVCS Letdown Line Break - Regenerative Heat Exchanger Subcompartment Blowdown	6.2-93
6.2.1.2-1 (Item P)	Short-Term Mass and Energy Release Rates for Subcompartment Analysis for RHR 12" Line DEG	6.2-94
6.2.1.2-1 (Item Q)	Short-Term Mass and Energy Release Rates for Subcompartment Analysis for FW 16" DEG Break at SG Nozzle Connection, HFP, FW @ 460 °F	6.2-102

STPEGS UFSAR

LIST OF TABLES (Continued)

CHAPTER 6

<u>Table</u>	<u>Title</u>	<u>Page</u>
6.2.1.2-5A	Steam Generator Loop Compartment Peak Pressure Summary for RHR Line Break Analysis	6.2-103
6.2.1.2-5B	Steam Generator Loop Compartment Peak Pressure Summary for FWLB Analysis	6.2-105
6.2.1.2-6	Steam Generator Loop Compartment Pressure - Junction Properties for RHR/SI Analysis (42-Node Model)	6.2-106
6.2.1.2-6A	Steam Generator Loop Compartment Pressure Analysis - Junction Properties for FWLB Analysis	6.2-110
6.2.1.2-7A	Steam Generator Loop Compartment Analysis - Force Coefficient (Area Projections) for Steam Generator Subjected to RHR Line Break	6.2-113
6.2.1.2-7B	Steam Generator Loop Compartment Analysis - Moment Coefficient (Area Projections) for Steam Generator Subjected to RHR Line Break	6.2-114
6.2.1.2-7C	Steam Generator Loop Compartment Analysis - Force Coefficient (Area Projections) for Steam Generator Subjected to FWLB	6.2-115
6.2.1.2-7D	Steam Generator Loop Compartment Analysis - Moment Coefficient (Area Projections) for Steam Generator Subjected to FWLB	6.2-116
6.2.1.2-8A	Steam Generator Loop Compartment Analysis - Force Coefficient (Area Projections) for Reactor Coolant Pump Subjected to RHR Line Break	6.2-117
6.2.1.2-8B	Steam Generator Loop Compartment Analysis - Moment Coefficient (Area Projections) for Reactor Coolant Pump Subjected to RHR Line Break	6.2-118
6.2.1.2-9	Pressurizer Subcompartment Analysis Spray Line Break	6.2-119
6.2.1.2-13	Main Steam Line and Feedwater Line Subcompartment Analysis	6.2-120
6.2.1.2-14	Main Steam Line and Feedwater Subcompartment Analysis Junction Description - Steam Line Break Analysis	6.2-121
6.2.1.2-15	Regenerative Heat Exchanger Subcompartment Nodal Description	6.2-122
6.2.1.2-16	Regenerative Heat Exchanger Subcompartment Junction Description	6.2-123
6.2.1.2-17	Radioactive Pipe Chase Subcompartment Nodal Description	6.2-124
6.2.1.2-18	Radioactive Pipe Chase Subcompartment Junction Description	6.2-125
6.2.1.2-19	RHR1A Valve Room Subcompartment Nodal Description	6.2-126
6.2.1.2-20	RHR1A Valve Room Subcompartment Junction Description	6.2-127

STPEGS UFSAR

LIST OF TABLES (Continued)

CHAPTER 6

<u>Table</u>	<u>Title</u>	<u>Page</u>
6.2.1.3-1	System Parameter Initial Conditions	6.2-128
6.2.1.3-2	Total Pumped ECCS Flow Rate for Two Trains of SI Operating	6.2-129
6.2.1.3-3	Total Pumped ECCS Flow Rate for Three Trains of SI Operating	6.2-130
6.2.1.3-4	Double-Ended Hot Let Break Blowdown Mass and Energy Releases	6.2-131
6.2.1.3-5	Double-Ended Pump Suction Break Blowdown Mass and Energy Releases	6.2-135
6.2.1.3-6	Decay Heat Curve Based on 1979 ANS Plus 2 Sigma Uncertainty	6.2-139
6.2.1.3-6A	Decay Heat Data Based on Standard Review Plan ASB 9-2 Correlations	6.2-140
6.2.1.3-7	Double-Ended Pump Suction Break Reflood Mass and Energy Releases (Two Train Case)	6.2-142
6.2.1.3-8	Double-Ended Pump Suction Break Reflood Mass and Energy Releases (Three Train Case)	6.2-148
6.2.1.3-9	Double-Ended Pump Suction Break Principal Parameters During Reflood (Two Train Case)	6.2-155
6.2.1.3-10	Double-Ended Pump Suction Break Principal Parameters During Reflood (Three Train Case)	6.2-157
6.2.1.3-11	Double-Ended Pump Suction Break Post-Reflood Mass and Energy Releases (Two Train Case)	6.2-159
6.2.1.3-12	Double-Ended Pump Suction Break Post-Reflood Mass and Energy Releases (Three Train Case)	6.2-162
6.2.1.3-13	Double-Ended Pump Suction Break Mass Balance (Two Train Case)	6.2-167
6.2.1.3-14	Double-Ended Pump Suction Break Mass Balance (Three Train Case)	6.2-168
6.2.1.3-15	Double-Ended Hot Let Break Mass Balance	6.2-169
6.2.1.3-16	Double-Ended Pump Suction Break Energy Balance (Two Train Case)	6.2-170
6.2.1.3-17	Double-Ended Pump Suction Break Energy Balance (Three Train Case)	6.2-171
6.2.1.3-18	Double-Ended Hot Leg Break Energy Balance	6.2-172

STPEGS UFSAR

LIST OF TABLES (Continued)

CHAPTER 6

<u>Table</u>	<u>Title</u>	<u>Page</u>
6.2.1.4-1	Mass and Energy Release Rates for Main Steam Line Break - 1.4 ft ² Double-Ended Rupture at 0% Power (Minimum Containment Heat Removal Systems)	6.2-173
6.2.1.4-2	Mass and Energy Release Rates for Main Steam Line Break - 1.4 ft ² Double-Ended Rupture at 3876 MWt Power (Minimum Containment Heat Removal Systems)	6.2-174
6.2.1.5-1	Blowdown Mass and Energy Releases	6.2-175
6.2.1.5-1a	Broken Loop Injection Spill During Blowdown	6.2-176
6.2.1.5-2	Reflood Mass and Energy Releases	6.2-177
6.2.1.5-3	Active Heat Sink Data for Minimum Post LOCA Containment Pressure	6.2-178
6.2.1.5-4	Passive Heat Sink Data for Minimum Post LOCA Containment Pressure	6.2-179
6.2.2-1	Containment Spray System - Design Parameters	6.2-181
6.2.2-2	Design Data for the Reactor Containment Fan Cooler (RCFC) System	6.2-182
6.2.2-3	Failure Modes and Effect Analysis - Containment Heat Removal Active Failure	6.2-185
6.2.2-4	CSS Pump NPSH Parameters	6.2-189
6.2.2-5	Estimate of CSS Spray Mass Flow Rates for Various Regions	6.2-190
6.2.4-1	Containment Isolation System Failure Modes and Effect Analysis	6.2-191

STPEGS UFSAR

LIST OF TABLES (Continued)

CHAPTER 6

<u>Table</u>	<u>Title</u>	<u>Page</u>
6.2.6-1	Systems Which Need not be Vented During Type A Testing	6.2-205
6.2.6-3	Containment Isolation Valves to be Leak Tested in Opposite Direction	6.2-207
6.3-1	Emergency Core Cooling System Component Parameters	6.3-32
6.3-2	ECCS Relief Valve Data	6.3-34
6.3-3	Motor-Operated Valves in ECCS	6.3-35
6.3-4	Materials Employed for Emergency Core Cooling System Components	6.3-37
6.3-5	Single Active Failure Analysis for Emergency Core Cooling System Components Short Term Phase	6.3-39
6.3-6	Emergency Core Cooling System Recirculation Piping - Passive Failure Analysis, Long-Term Phase	6.3-40
6.3-7	Manual Actions Required for Safety Injection Modes of Operation	6.3-41
6.3-8	Emergency Core Cooling System Shared Functions Evaluation	6.3-42
6.3-10	Emergency Core Cooling System - Safeguards Operations Failure Modes and Effects Analysis	6.3-43
6.3-11	ECCS Check Valves to be Leak Tested	6.3-48
6.3-12	ECCS Active Powered Components	6.3-49
6.3-13	Air-Operated Valves in the ECCS	6.3-51
6.3-14	Solenoid-Operated Valves in the ECCS	6.3-52
6.4-1	Equipment to Which the Control Room Operators Could Require Access During an Emergency	6.4-11
6.4-2	Control Room Dose Analysis	6.4-12
6.5-1	Comparison of Engineered Safety Feature Filter Systems with Regulatory Guide 1.52, Rev. 2, Requirements	6.5-11
6.5-2	Input Parameters for Determining Iodine Removal Coefficients	6.5-14
6.5-3	Input Parameters to Determine Minimum pH for Sump Solution	6.5-15
6.5-4	Input Parameters to Determine Maximum pH for Sump Solution	6.5-16

STPEGS UFSAR

LIST OF FIGURES

CHAPTER 6

<u>Figure Number</u>	<u>Title</u>	<u>Reference Number</u>
6.2.1.1-3	Fan Cooler Duty Curve Per Unit	
6.2.1.1-25	Containment Pressure - 1.4 ft ² DER MSLB	
6.2.1.1-27	Containment Temperature - 1.4 ft ² DER MSLB	
6.2.1.1-28	Condensing Heat Transfer Coefficient - 1.4 ft ² DER MSLB	
6.2.1.1-29	Total Containment Atmosphere Energy - 1.4 ft ² DER MSLB	
6.2.1.1-30	Containment Pressure – LOCA DEHL	
6.2.1.1-31	Containment Temperatures – LOCA DEHL	
6.2.1.1-32	Heat Transfer Coefficient – LOCA DEHL	
6.2.1.1-33	Containment Pressure –LOCA DEPSG (Minimum SI)	
6.2.1.1-34	Containment Temperatures - LOCA DEPSG (Minimum SI)	
6.2.1.1-35	Heat Transfer Coefficient - LOCA DEPSG (Minimum SI)	
6.2.1.1-36	Containment Pressure - LOCA DEPSG (Maximum SI)	
6.2.1.1-37	Containment Temperatures - LOCA DEPSG (Maximum SI)	
6.2.1.1-38	Heat Transfer Coefficient - LOCA DEPSG (Maximum SI)	

*** The drawings below are reference drawings only and are not to be revised.**

6.2.1.2-3	Steam Generator Loop Compartment Node Arrangement	
	El. (-)11'33" - (Sheet 1 of 8)	6C18-9-N-05001-2*
	El. (-)2'-0" - (Sheet 2 of 8)	6C18-9-N-05002-2*
	El. 19'0" - (Sheet 3 of 8)	6C18-9-N-05003-2*
	El. (-)37'3" - (Sheet 4 of 8)	6C18-9-N-05004-2*
	El. 52'0" - (Sheet 5 of 8)	6C18-9-N-05005-1*
	El. 68'0" - (Sheet 6 of 8)	6C18-9-N-05006-2*
	Section AA - (Sheet 7 of 8)	6C18-9-N-05007-3*
	Section BB - (Sheet 8 of 8)	6C18-9-N-05008-2*

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 6

<u>Figure Number</u>	<u>Title</u>	<u>Reference Number</u>
6.2.1.2-4	Pressurizer Compartment Nodes Between: El. 69'-9" & 85'-0" - (Sheet 1 of 3) El. 46'-7" & 69'-9" - (Sheet 2 of 3) (Sheet 3 of 3)	6C18-9-N-05006-4* 6C18-9-N-05005-2* 6C18-9-N-05008-4*
6.2.1.2-5	Surge Line Subcompartment Nodes Between: El. 46'-4" & 69'-9" - (Sheet 1 of 5) El. 37'-3" & 43'-4" - (Sheet 2 of 5) El. 19'-0" & 37'-3" - (Sheet 3 of 5) El. 5'-9" & 19'-0" - (Sheet 4 of 5) (Sheet 5 of 5)	6C18-9-N-05005-2* 6C18-9-N-05004-3* 6C18-9-N-05003-3* 6C18-9-N-05002-3* 6C18-9-N-05008-2*
6.2.1.2-6	Main Steamline and Feedwater Line Subcompartment Nodes Between: El. 19'-0" & 37'-3" - (Sheet 1 of 3) El. 37'-3" & 52'-0" - (Sheet 2 of 3) El. 52'-0" & 68'-0" - (Sheet 3 of 3)	6C18-9-N-05003-3* 6C18-9-N-05004-3* 6C18-9-N-05005-2*
6.2.1.2-7	Regenerative Heat Exchanger Subcompartment Nodes Between El. 37'-3" & 52'-0"	6C18-9-N-05004-4*
6.2.1.2-8	Radioactive Pipe Chase Between Elevations 29' & 37'-3"	5C15-9-P-05029-1*
6.2.1.2-9	RHR 1A and 1B Valve Room Subcompartment Nodes Between: El. 37'3" and 52'0" - (Sheet 1 of 2) (Sheet 2 of 2)	6C18-9-N-05004-4* 6C18-9-N-05003-4*
6.2.1.2-11	Node and Junction Diagram for Steam Loop Compartment (4 Sheets)	
6.2.1.2-11A	Nodalization Diagram for Steam Generator Loop Compartment for FWLB Analysis (8 sheets)	
6.2.1.2-12	Pressurizer Subcompartment Nodal Model	
6.2.1.2-13	Surge Line Subcompartment Nodal Model	

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 6

<u>Figure Number</u>	<u>Title</u>	<u>Reference Number</u>
6.2.1.2-14	Main Steam and Feedwater Line Subcompartment Nodal Model	
6.2.1.2-15	Regenerative Heat Exchanger Subcompartment Nodal Model	
6.2.1.2-16	Radioactive Pipe Chase Subcompartment Nodal Model	
6.2.1.2-17	RHR Valve Room Subcompartment Nodal Model	
6.2.1.2-20A	Steam Generator Loop Compartment Pressurization Analysis, 12" RHR Break in Node 15 (11 sheets)	
6.2.1.2-20B	Steam Generator Loop Compartment Pressurization Analysis, 12" RHR Break in Node 4 (11 sheets)	
6.2.1.2-20C	Steam Generator Loop Compartment Pressurization Analysis, 12" RHR Break in Node 12 (11 sheets)	
6.2.1.2-20D	Steam Generator Loop Compartment Pressurization Analysis, 16" FWLB (Nodes 1& 17)	
6.2.1.2-21A	Steam Generator Forces and Moments Analysis – Steam Generator Forces due to RHR Break in Nodes 15 (6 sheets)	
6.2.1.2-21B	Steam Generator Loop Compartment Forces and Moments on Steam Generator due to FWLB (11 sheets)	

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 6

<u>Figure Number</u>	<u>Title</u>	<u>Reference Number</u>
6.2.1.2-22A	Reactor Coolant Pump Forces and Moments due to RHR Break in Node 15 (6 sheets)	
6.2.1.2-23	Pressurizer P-T Analysis (3 Sheets)	
6.2.1.2-25	MSLB Subcompartment P-T Analysis (2 Sheets)	
6.2.1.2-26	MFWLB Subcompartment Analysis (2 sheets)	
6.2.1.2-27	Calculated Pressures Regenerative Heat Exchanger Subcompartment	
6.2.1.2-28	Calculated Pressures Radioactive Pipe Chase Subcompartment	
6.2.1.2-29	Calculated Pressures RHR 1A & 1B Valve Room Subcompartment	
6.2.1.2-30	Steam Generator Loop Compartment Force and Moment Coordinate System	
6.2.1.5-1	STPEGS Large Break LOCA Analysis, DECLG $C_D=0.8$, SI, High T_{AVG} , Containment Backpressure	
6.2.1.5-2	Containment Fan Cooler Performance Curves	

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 6

<u>Figure Number</u>	<u>Title</u>	<u>Reference Number</u>
6.2.1.5-3	STPEGS Large Break LOCA Analysis, DECLG $C_D=0.8$, Min SI, High T_{AVG} , Containment Heat Transfer Coefficient	
6.2.2-1	P&ID Containment Spray System	5N10-9-F-05037#1 5N10-9-F-05037#2
6.2.2-3	Composite Piping, Reactor Containment Building - Plan - El. 83'-0" - Area 12 (Sheet 1 of 4)	5C15-9-P-05025-6
	Plan - El. 83'-0" - Area 13 (Sheet 2 of 4)	5C15-9-P-05026-5
	Plan - El. 83'-0" - Area 14 (Sheet 3 of 4)	5C15-9-P-05027-5
	Plan - El. 83'-0" - Area 15 (Sheet 4 of 4)	5C15-9-P-05028-6
6.2.2-4	P&ID HVAC Reactor Containment Building, Fan Coolers Subsystem	5V14-9-V-00016#1 5V14-9-V-00016#2
6.2.2-6	Reactor Containment Building CSS Spray Coverage Plan - El. (-)11'-3"	6C18-9-N-05001-2*
6.2.2-7	Reactor Containment Building CSS Spray Coverage Plan - El. (-)2'-0"	6C18-9-N-05002-2*
6.2.2-8	Reactor Containment Building CSS Spray Coverage Plan - El. 19'-0"	6C18-9-N-05003-2*
6.2.2-9	Reactor Containment Building CSS Spray Coverage Plan - El. 37'-3"	6C18-9-N-05004-2*
6.2.2-10	Reactor Containment Building CSS Spray Coverage Plan - El. 52'-0"	6C18-9-N-05005-1*

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 6

<u>Figure Number</u>	<u>Title</u>	<u>Reference Number</u>
6.2.2-11	Reactor Containment Building CSS Spray Coverage Plan - El. 68'-0"	6C18-9-N-05006-2*
6.2.2-12	Reactor Containment Building CSS Spray Coverage Section B-B	6C18-9-N-05007-1*
6.2.2-13	HVAC Reactor Containment Building Plan El. (-)11'-3" Area 13	5V14-9-V-00083
6.2.2-14	HVAC Reactor Containment Building Enlarged Plant and Section RCFC	5V14-9-V-00090
6.2.4-1	Containment Penetrations (100 Sheets)	
6.2.4-2	Arrangement of Sump Piping	
6.2.6-1	P&ID Containment Leak Rate Test (CLRT) Pressurization System	5C56-0-F-05058
6.3-1	P&ID Safety Injection System	5N12-9-F-05013#1 5N12-9-F-05013#2
6.3-2	P&ID Safety Injection System	5N12-9-F-05014#1 5N12-9-F-05014#2
6.3-3	P&ID Safety Injection System	5N12-9-F-05015#1 5N12-9-F-05015#2
6.3-4	P&ID Safety Injection System	5N12-9-F-05016#1 5N12-9-F-05016#2
6.3-5	Emergency Core Cooling System, Process Flow Diagram	
6.3-6	Low Head SI Pump Performance Curves	
6.3-7	High Head SI Pump Performance Curve	

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 6

<u>Figure Number</u>	<u>Title</u>	<u>Reference Number</u>
6.3-8	RWST Level Setpoints	
6.4-1	Control Room Envelope	
6.4-2	Control Room Layout	
6.5-1	Containment Sump pH vs. Time	
6.5-2	Drop Size Distribution for the Sprayed Region	