



KEY PLAN

* SPRINKLERS INSTALLED IN ACCORDANCE WITH "NFPA - 13".
 FIRE ZONE ABOVE FIRE RATED FLOOR SLAB : 1-5A-S, 1-5E & 1-5A-W.
 FIRE ZONE BELOW FIRE RATED FLOOR SLAB : 1-4A-W.

[CROSS-HATCHING] [CABLE TRAY - ALL TRAYS ARE 24" WIDE OR LESS, UNLESS NOTED OTHERWISE.]
 [DIAGONAL HATCHING] [CROSS HATCHING REPRESENTS FIRE RATED FLOOR SLAB.]

C-201	E-105239
C-202	E-105240
E-29-4	E-107630 SH.4
C-307	E-105314
RE DRAWING NO.	PP&L DRAWING NO.
REFERENCE DRAWINGS	

0	INITIAL ISSUE	T ₀	W ₀	F ₀	JAG	10/24/86
REV	DESCRIPTION	DR	CH	APPROVED	DATE	

NON-QUALITY RELATED DWG. CLASS 3

SUSQUEHANNA S.E.S.
 UNIT # 1
 REACTOR BUILDING
 APPENDIX R-DEVIATION REQ. #6
 FIRE RATED FL. SLAB EL. 749'-1

AREA 29 | ELEV. 749'-1 | SCALE: NOTED

PENNSYLVANIA POWER & LIGHT COMPANY
 ALLENTOWN PA.

PP&L DRAWING NO.	SHEET NO.	REV. NO.
C-206008	1	0
RE DRAWING NO.	C-1768	

PARTIAL PLAN BELOW EL. 749'-1"
 T.O.S. EL. 747'-4" U.N.O.
 SCALE: 1/4" = 1'-0"

PP&L FORM 3505C (1/84)

80712

86-11060242