GENERAL ELECTRIC 80IE276 SHEET 3 OF 3 REV NO. 2

UNLESS OTHERWISE SPECIFIED USE THE FOLLOWING:— APPLIED PRACTICES | SURFACES ✓ | TOLERANCES ON MACHINED DIMENSIONS: FRACTIONS ± | DECIMALS ± | ANGLES ±

TITLE ARRGT CONTROL ROOM PANEL 103

FIRST MADE FOR HUTCHINSON ISLAND UNIT 1

REMOVABLE COVER ACCESS TO WIRING AREA

24, 12 PT TERM BD, G.E. TYPE EB-5-TYP

22, PLASTIC COATED WIRE GRILLE-TYP "SB" FUSE BOX

REAR (AISLE SIDE)

4.00 EA. END | 39.50 | 8.00 | 12.00 | 5.00 | 3.50

DD, CC, BB, EE, FF, TT, AA, 23

N

22.75 | 13.00

SEE CLOCK MOUNTING DETAIL, 89

PARTIAL SECTION J-J

29.62 ⚠ REMOVE EXISTING STIFFENER, ADD STIFFENER | 41.00 | ADD STIFFENER | 52.00 ⚠ | 53.62 | 63.00

59.00 REF | 46.72 | 46.25

ANNUNCIATOR 6 WINDOWS HIGH 6 WINDOWS WIDE 2 PLACES

QSPDS "B" DISPLAY

36.50 | 15.40 | 56.30 | 50.40 | 64.16

33.00 | 27.00 | 21.00 | 15.00 | 8.00 | 3.90

TD-101, TD-105, TD-109, TD-113

| | | |