## U.S. NUCLEAR REGULATORY COMMISSION

## **MATERIALS LICENSE**

Pursuant to the Atomic Energy Act of 1954, as amended, the Energy Reorganization Act of 1974 (Public Law 93-438), and Title 10, Code of Federal Regulations, Chapter I, Parts 30, 31, 32, 33, 34, 35, 36, 37, 39, 40, 70 and 71, and in reliance on statements and representations heretofore made by the licensee, a license is hereby issued authorizing the licensee to receive, acquire, possess, and transfer byproduct, source, and special nuclear material designated below; to use such material for the purpose(s) and at the place(s) designated below; to deliver or transfer such material to persons authorized to receive it in accordance with the regulations of the applicable Part(s). This license shall be deemed to contain the conditions specified in Section 183 of the Atomic Energy Act of 1954, as amended, and is subject to all applicable rules, regulations, and orders of the Nuclear Regulatory Commission now or hereafter in effect and to any conditions specified below.

and orders of the Nuclear Regulatory Commission now or hereafter in effect and to any conditions specified below.								
1.	Licensee  1. R & M Engineering - Ketchikan, Inc.			In accordance with letter dated June 25, 2018		4. Expiration Date: October 31, 2032		
2.	7180 Revilla Road Suite 300 Ketchikan, AK 99901		SAJO	3. License amende follows:		nber: 50-29259-01 is its entirety to read as		ret No.: 030-37441 rence No.:
6.	Byproduct, source, and/or special nuclear material	7.	Chemical and/or physical fo	orm	8.	Maximum amount that licens may possess at any one time under this license		Authorized use
Α.	Cesium-137	A.	Sealed Sources (AEA Technology/QSA, Inc., M CDCW556; Isotope Prod Laboratories, Model HEC	uct	<b>A</b> .	9 millicuries per source and 45 millicuries total	A.	For use in Troxler Electronic Laboratories, Inc. Model 3400 Series portable gauging devices for measuring physical properties of materials.
B.	Americium-241/ Beryllium	B.	Sealed Neutron Source ( Technology/QSA, Inc., M AMNV.997; Isotope Prod Laboratories, Model Am1 3021, or 3027)	odel luct	B.	44 millicuries per source and 220 millicuries total	B.	For use in Troxler Electronic Laboratories, Inc. Model 3400 Series portable gauging devices for measuring physical properties of materials.
C.	Cesium-137	C.	Sealed Sources (CPN International, Inc., Model CPN-131)		C.	10 millicuries per source and 50 millicuries total	C.	For use in CPN International, Inc. Model MC Series PORTAPROBE portable gauging devices for measuring physical properties of materials.
D.	Americium-241/ Beryllium	D.	Sealed Sources (CPN International, Inc., Model CPN-131)		D.	50 millicuries per source and 250 millicuries total	D.	For use in CPN International, Inc. Model MC Series PORTAPROBE portable gauging devices for measuring physical properties of materials.

NRC FORM 374A	U.S. NUCLEAR REGULATORY COMM	ISSION	PAGE 2 OF 5 PAGES
MATERIALS LICENSE	License Number 50-29259-01	Docket or Reference Number 030-37441	
SUPPLEMENTARY SHEET	Amendment No. 6		

## CONDITIONS

10. Licensed material may be used or stored at the licensee's facilities located at 7180 Revilla Road, Ketchikan, Alaska, 99901

Licensed material may be used at temporary job sites anywhere in the United States where the U.S. Nuclear Regulatory Commission maintains jurisdiction for regulating the use of licensed material, including areas of exclusive Federal jurisdiction within Agreement States. If the jurisdiction status of a Federal facility within an Agreement State is unknown, the licensee should contact the Federal agency controlling the job site in question to determine whether the proposed job site is an area of exclusive Federal jurisdiction. Authorization for use of radioactive materials at job sites in Agreement States not under exclusive Federal jurisdiction shall be obtained from the appropriate state regulatory agency.

- 11. Licensed material shall only be used by, or under the supervision and in the physical presence of, individuals who have received the training described in the letter dated July 21, 2017. The licensee shall maintain records of individuals designated as users for 3 years following the last use of licensed material by the individual.
- 12. The Radiation Safety Officer (RSO) for this license is Trevor Sande.
- 13. A. Sealed sources and detector cells shall be tested for leakage and/or contamination at intervals not to exceed the intervals specified in the certificate of registration issued by the U.S. Nuclear Regulatory Commission under 10 CFR 32.210 or by an Agreement State. In the absence of a registration certificate, sealed sources shall be tested for leakage and/or contamination at intervals not to exceed 6 months, or at such other intervals as specified.
  - B. Notwithstanding Paragraph A of this Condition, sealed sources designed to primarily emit alpha particles shall be tested for leakage and/or contamination at intervals not to exceed 3 months.

NRC FORM 374A	U.S. NUCLEAR REGULATORY COMM	ISSION	PAGE 3 OF 5 PAGES
MATERIALS LICENSE	License Number 50-29259-01	Docket or Reference Number 030-37441	
SUPPLEMENTARY SHEET	Amendment No. 6		

- C. In the absence of a certificate from a transferor indicating that a leak test has been made within the intervals specified in the certificate of registration issued by the U.S. Nuclear Regulatory Commission under 10 CFR 32.210 or by an Agreement State, prior to the transfer, a sealed source received from another person shall not be put into use until tested and the test results received.
- D. Sealed sources need not be tested if they contain only hydrogen-3; or they contain only a radioactive gas; or the half-life of the isotope is 30 days or less; or they contain not more than 100 microcuries of beta- and/or gamma-emitting material or not more than 10 microcuries of alpha-emitting material.
- E. Sealed sources need not be tested if they are in storage and are not being used. However, when they are removed from storage for use or transferred to another person, and have not been tested within the required leak test interval, they shall be tested before use or transfer. No sealed source shall be stored for a period of more than 10 years without being tested for leakage and/or contamination.
- F. The leak test shall be capable of detecting the presence of 185 becquerels (0.005 microcuries) of radioactive material on the test sample. If the test reveals the presence of 185 becquerels (0.005 microcuries) or more of removable contamination, a report shall be filed with the U.S. Nuclear Regulatory Commission in accordance with 10 CFR 30.50(c)(2), and the source shall be removed immediately from service and decontaminated, repaired, or disposed of in accordance with Commission regulations.
- G. Analysis of leak test samples and/or contamination shall be performed by persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services. The licensee is authorized to collect leak test samples but not perform the analysis.
- H. Records of leak test results shall be kept in units of becquerels (microcuries) and shall be maintained for 3 years.
- 14. Sealed sources containing licensed material shall not be opened sources removed from source holders by the licensee, except as specifically authorized.

NRC FORM 374A	U.S. NUCLEAR REGULATORY COMM	ISSION	PAGE 4 OF 5 PAGES
MATERIALS LICENSE	License Number 50-29259-01	Docket or Reference Number 030-37441	
SUPPLEMENTARY SHEET	Amendment No. 6		

- 15. The licensee shall conduct a physical inventory every 6 months, or at other intervals approved by the U.S. Nuclear Regulatory Commission, to account for all sealed sources and/or devices received and possessed under the license. Records of inventories shall be maintained for 3 years from the date of each inventory, and shall include the radionuclides, quantities, manufacturer's name and model numbers, and the date of the inventory.
- 16. Except for maintaining labeling as required by 10 CFR Part 20, or Part 71, the licensee shall obtain authorization from the U.S. Nuclear Regulatory Commission before making any changes in the sealed source, device, or source-device combination that would alter the description or specifications as indicated in the respective certificate of registration issued either by the U.S. Nuclear Regulatory Commission pursuant to 10 CFR 32.210 or by an Agreement State.
- 17. Each portable nuclear gauge shall have a lock or outer locked container designed to prevent unauthorized or accidental removal of the sealed source from its shielded position. The gauge or its container must be locked when in transport, storage or when not under the direct surveillance of an authorized user.
- 18. Any cleaning, maintenance, or repair of the gauge(s) that requires detaching the source or source rod from the gauge shall be performed only by the manufacturer or by other persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services.

NRC FORM 374A	U.S. NUCLEAR REGULATORY COMM	ISSION PAGE 5 OF 5 PAGES		
MATERIALS LICENSE	License Number 50-29259-01	Docket or Reference Number 030-37441		
SUPPLEMENTARY SHEET	Amendment No. 6			
representations, and procedures contain those procedures that are required to be	ed in the documents, including any enclosubmitted in accordance with the regula ments, representations, and procedures  (ML17128A505) A084) (306A135) 100A088)	ct its program in accordance with the statements, business, listed below. This license condition applies only to tions. The U.S. Nuclear Regulatory Commission's in the licensee's application and correspondence are more		
FOR THE U.S. NUCLEAR REGULATORY COMMISSION				
	_	/RA/		
Date: September 21, 2018	By: _ .I.	acqueline D. Cook		
		Region IV		